


# AcousticLUX 1

## TECHNICAL DATA SHEET

1500 x 50 x 99mm

- Suspended decorative LED luminaire
- Light Distribution: Direct/Indirect
- Optical System: Opal polycarbonate diffuser
- Housing: Aluminium
- Colour: Made to customers specification, see page 3 for options



### ELECTRICAL DATA

Main Voltage:	220-240V, 0/50/60Hz
Power Factor:	>0,95
Integrated Sensor:	Available

System power*, W:	21w to 54.9w
Control gear:	ECG On/off or Dali

### LIGHTING DATA

Luminaire output*, lm(ta+25°C):	2600; m to 6400lm
CRI (Ra):	80+, CRI90 on request
SDCM:	3
Distribution Type:	Direct
UGR Index:	<19

System efficacy, lm/W:	Up to 128
CCT, K:	4000
Light Distribution:	Wide-wide beam
Beam angle, °:	109x109
LED lifetime, h:	50000/L80B10

### TECHNICAL DATA

Dimensions, mm:	L1439 W50 H99
Net weight, kg:	3.9 up to 4.8

Quantity in package, pcs:	1
---------------------------	---

### STANDARDS

Operating temperature range, °C:	ta0...+35
Ingress protection code:	IP40


Mechanical impact resistance:	IK05
Certificates:	CE, ROHS

**Note:** Tolerance range for optical and electrical data: ±10%. MERIT LIGHTING SOLUTIONS is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification.


# AcousticLUX 1

## TECHNICAL DATA SHEET

### TECHNICAL DRAWING



### LIGHT DISTRIBUTION CURVE



### PRODUCTS

COLOUR (K)	LUMINAIRE OUTPUT (LLM)	POWER (W)	EFFICACY (LLM/W)	PART CODE
4000	3392	26.4	128	ACLX1/15/3400/4K
4000	4622	37.8	122	ACLX1/15/4600/4K
4000	6354	54.9	116	ACLX1/15/6400/4K

### OPTIONS

	PART CODE		PART CODE
DALI driver	/DD	MeritMESH with Sensor	/MMS
3 Hour emergency	/E3S	Integrated DALI sensor	/IDS
3 hour DALI emergency	/E3D	Custom RAL	/RAL
MeritMESH	/MM		

EXAMPLE PART CODE: **ACLX1/12/2600/4K/DD/E3D**

**Note:** Tolerance range for optical and electrical data: ±10%. MERIT LIGHTING SOLUTIONS is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification.

# AcousticLUX 1

## TECHNICAL DATA SHEET

### Material Colour:



### Natural colour:



**Note:** Tolerance range for optical and electrical data:  $\pm 10\%$ . MERIT LIGHTING SOLUTIONS is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification.