


# AcousticLUX 2

## TECHNICAL DATA SHEET

1200 x 1200mm

- Decorative Acoustic ring shaped LED luminaire
- Light Distribution: Direct
- Optical System: Opal PMMA diffuser
- Housing: Steel
- Colour: Made to customers specification, see page 3 for options



### ELECTRICAL DATA

Main Voltage:	220-240V, 0/50/60Hz
Power Factor:	>0,95
Integrated Sensor:	Available

System power*, W:	34.8w to 72.4w
Control gear:	ECG On/off or Dali

### LIGHTING DATA

Luminaire output*, lm(ta+25°C):	4200lm to 8200lm
CRI (Ra):	80+, CRI90 on request
SDCM:	3
Distribution Type:	Direct
UGR Index:	<19

System efficacy, lm/W:	Up to 126
CCT, K:	3000K to 4000K
Light Distribution:	Symmetrical wide beam
Beam angle, °:	105
LED lifetime, h:	50000/L80B10

### TECHNICAL DATA

Dimensions, mm:	L1200 W1200 H80
Net weight, kg:	14.9

Quantity in package, pcs:	1
---------------------------	---

### STANDARDS

Operating temperature range, °C:	ta0...+35
Ingress protection code:	IP40


Mechanical impact resistance:	IK02
Certificates:	CE, ROHS

**Note:** Tolerance range for optical and electrical data: ±10%. MERIT LIGHTING SOLUTIONS is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification.


# AcousticLUX 2

## TECHNICAL DATA SHEET

### TECHNICAL DRAWING



### LIGHT DISTRIBUTION CURVE



### PRODUCTS

COLOUR (K)	LUMINAIRE OUTPUT (LLM)	POWER (W)	EFFICACY (LLM/W)	PART CODE
3000	4197	34.8	121	ACLX2/1212/4200/3K
3000	5719	49.8	115	ACLX2/1212/5700/3K
3000	7861	72.4	109	ACLX2/1212/7900/3K
4000	4394	34.8	126	ACLX2/1212/4400/4K
4000	5987	49.8	120	ACLX2/1212/6000/4K
4000	8231	72.4	114	ACLX2/1212/8200/4K

### OPTIONS

	PART CODE		PART CODE
DALI driver	/DD	MeritMESH with Sensor	/MMS
3 Hour emergency	/E3S	Integrated DALI sensor	/IDS
3 hour DALI emergency	/E3D	Custom RAL	/RAL
MeritMESH	/MM		

EXAMPLE PART CODE: **ACLX2/1212/4400/4K/DD/E3D**

**Note:** Tolerance range for optical and electrical data:  $\pm 10\%$ . MERIT LIGHTING SOLUTIONS is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification.

# AcousticLUX 2

## TECHNICAL DATA SHEET

### Material Colour:



### Natural colour:



**Note:** Tolerance range for optical and electrical data:  $\pm 10\%$ . MERIT LIGHTING SOLUTIONS is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification.