

AcousticLUX 4

TECHNICAL DATA SHEET

1180 x 1180 x 68mm

- Suspended acoustic LED luminaire
- Light Distribution: Direct
- Optical System: Opal polycarbonate diffuser
- Housing: Aluminium
- Colour: White (RAL9003S), custom RAL available, see page 3 for options



ELECTRICAL DATA

| | |
|--------------------|---------------------|
| Main Voltage: | 220-240V, 0/50/60Hz |
| Power Factor: | >0,95 |
| Integrated Sensor: | Available |

| | |
|-------------------|--------------------|
| System power*, W: | 24.8w to 103.7w |
| Control gear: | ECG On/off or Dali |

LIGHTING DATA

| | |
|---------------------------------|-----------------------|
| Luminaire output*, lm(ta+25°C): | 3200lm TO 11700lm |
| CRI (Ra): | 80+, CRI90 on request |
| SDCM: | 3 |
| Distribution Type: | Direct |
| UGR Index: | <19 |

| | |
|------------------------|--------------|
| System efficacy, lm/W: | Up to 130 |
| CCT, K: | 4000 |
| Light Distribution: | Direct |
| LED lifetime, h: | 50000/L80B10 |

TECHNICAL DATA

| | |
|-----------------|-----------------|
| Dimensions, mm: | L1180 W1180 H68 |
| Net weight, kg: | 13.4 |

| | |
|---------------------------|---|
| Quantity in package, pcs: | 1 |
|---------------------------|---|

STANDARDS

| | |
|----------------------------------|------------|
| Operating temperature range, °C: | ta15...+35 |
| Ingress protection code: | IP40 |


| | |
|-------------------------------|----------|
| Mechanical impact resistance: | IK05 |
| Certificates: | CE, ROHS |

Note: Tolerance range for optical and electrical data: ±10%. MERIT LIGHTING SOLUTIONS is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification.


AcousticLUX 4

TECHNICAL DATA SHEET

TECHNICAL DRAWING



LIGHT DISTRIBUTION CURVE



PRODUCTS

| COLOUR (K) | LUMINAIRE OUTPUT (LLM) | POWER (W) | EFFICACY (LLM/W) | PART CODE |
|------------|------------------------|-----------|------------------|---------------------|
| 4000 | 6295 | 48.5 | 130 | ACLX4/1212/6300/4K |
| 4000 | 8567 | 70 | 122 | ACLX4/1212/8600/4K |
| 4000 | 11618 | 103.7 | 112 | ACLX4/1212/11700/4K |

OPTIONS

| | PART CODE | | PART CODE |
|-----------------------|-----------|------------------------|-----------|
| DALI driver | /DD | MeritMESH with Sensor | /MMS |
| 3 Hour emergency | /E3S | Integrated DALI sensor | /IDS |
| 3 hour DALI emergency | /E3D | Custom RAL | /RAL |
| MeritMESH | /MM | | |

EXAMPLE PART CODE: **ACLX4/66/3200/4K/DD/E3D**

Note: Tolerance range for optical and electrical data: ±10%. MERIT LIGHTING SOLUTIONS is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification.

AcousticLUX 4

TECHNICAL DATA SHEET

Material Colour:



Natural colour:



Note: Tolerance range for optical and electrical data: $\pm 10\%$. MERIT LIGHTING SOLUTIONS is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification.