

SurfaceLUX 1

TECHNICAL DATA SHEET

1200 x 175mm

- Surface Lighting
- Surface mounted LED luminaire
- Light Distribution: Direct
- Optical System: Matt micro-prismatic PMMA diffuser
- Housing: Steel
- Colour: White (RAL 9003S)



ELECTRICAL DATA

Main Voltage:	220-240V, 0/50/60Hz	System power*, W:	26.1w to 42.7w
Power Factor:	>0,95	Control gear:	ECG On/off or Dali
Integrated Sensor:	Available		

LIGHTING DATA

Luminaire output*, lm(ta+25°C):	3400lm to 5800lm	System efficacy, lm/W:	Up to 142
CRI (Ra):	80+, CRI90 on request	CCT, K:	3000K to 4000K
SDCM:	3	Light Distribution:	Wide-wide beam
Distribution Type:	Direct	Beam angle, °:	89x90
UGR Index:	<19	LED lifetime, h:	50000/L80B10

TECHNICAL DATA

Dimensions, mm:	L1203 W175 H47	Quantity in package, pcs:	1
Net weight, kg:	3.9		

STANDARDS


Operating temperature range, °C:	ta0...+35	Mechanical impact resistance:	IK05
Ingress protection code:	IP44	Certificates:	CE, ROHS

Note: Tolerance range for optical and electrical data: ±10%. MERIT LIGHTING SOLUTIONS is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification.


SurfaceLUX 1

TECHNICAL DATA SHEET

TECHNICAL DRAWING



LIGHT DISTRIBUTION CURVE



PRODUCTS

COLOUR (K)	LUMINAIRE OUTPUT (LLM)	POWER (W)	EFFICACY (LLM/W)	PART CODE
3000	3376	26.1	129	SLX1/12/3400/3K
3000	4824	35.5	136	SLX1/12/4800/3K
3000	5525	42.7	129	SLX1/12/5500/3K
4000	3534	26.1	136	SLX1/12/3500/4K
4000	5051	35.5	142	SLX1/12/5100/4K
4000	5785	42.7	135	SLX1/12/5800/4K

OPTIONS

	PART CODE		PART CODE
DALI driver	/DD	MeritMESH with Sensor	/MMS
3 Hour emergency	/E3S	Integrated DALI sensor	/IDS
3 hour DALI emergency	/E3D	Custom RAL	/RAL
MeritMESH	/MM		

EXAMPLE PART CODE: **SLX1/12/3500/4K/DD/E3D**

Note: Tolerance range for optical and electrical data: $\pm 10\%$. MERIT LIGHTING SOLUTIONS is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification.