

ArcLUX 13

TECHNICAL DATA SHEET

135mm

- Mini linear downlight, Low glare, ultra slim
- Light Distribution: Direct/Adjustable
- Optical System: 30° medium beam lens
- Housing: Aluminium
- Colour: White Bezel, Black Baffle



ELECTRICAL DATA

Main Voltage:	220-240V, 0/50/60Hz
Power Factor:	>0,95
Integrated Sensor:	Available

System power*, W:	13.5w to 22.9w
Control gear:	ECG On/off or Dali

LIGHTING DATA

Luminaire output*,lm(ta+25°C):	1049lm to 2099lm
CRI (Ra):	CRI90
SDCM:	3
Distribution Type:	Direct
UGR Index:	<14

System efficacy, lm/W:	Up to 91.5
CCT, K:	3000 to 4000
Light Distribution:	Direct
Beam Angle °:	30° (10°, 15° and 50° available)
LED lifetime, h:	60000/L80/F50

TECHNICAL DATA

Dimensions, mm:	L:349mm W:80mm H:62mm
Net weight, kg:	1.2

Quantity in package, pcs:	1
---------------------------	---

STANDARDS

Operating temperature range, °C:	ta -25...+35
Ingress protection code:	IP44

Certificates:	CE, ROHS
---------------	----------

Note: Tolerance range for optical and electrical data: $\pm 10\%$. 4C LIGHTING SOLUTIONS is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification.

