

VandalLUX 1

1500mm

- Surface mounted, vandal resistant, frame with stainless steel security screws
- Light Distribution: Direct
- Optical System: Opal Polycarbonate Diffuser
- Housing: Zinc Plated Steel
- Colour: White



TECHNICAL DATA SHEET

ELECTRICAL DATA

Main Voltage:	220-240V, 0/50/60Hz
Power Factor:	>0,90
Integrated Sensor:	Available

System power*, W:	30.6w to 54.1w
Control gear:	ECG On/off or Dali

LIGHTING DATA

Luminaire output*,lm(ta+25°C):	3691 to 7023
CRI (Ra):	80+
SDCM:	3
Distribution Type:	Direct
UGR Index:	<22

System efficacy, lm/W:	Up to 130
CCT, K:	3000 to 4000
Light Distribution:	Direct
Beam angle, °:	106x106
LED lifetime, h:	100000/L80B10

TECHNICAL DATA

Dimensions, mm:	L:1550 H:150 W:65
Net weight, kg:	9.2

Quantity in package, pcs:	1
---------------------------	---


STANDARDS

Operating temperature range, °C:	ta -20... +40
Ingress protection code:	IP65


Mechanical impact resistance:	IK10+
Certificates:	CE, UKCA, RoHS

Note: Tolerance range for optical and electrical data: $\pm 10\%$. 4C LIGHTING SOLUTIONS is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification.

TECHNICAL DRAWING



LIGHT DISTRIBUTION CURVE



PRODUCTS

COLOUR (K)	LUMINAIRE OUTPUT (LLM)	POWER (W)	EFFICACY (LLM/W)	PART CODE
3000	3691	30.6	120	VLX1/1500/3690/3K
3000	5023	40.8	123	VLX1/1500/5020/3K
3000	5507	45.5	121	VLX1/1500/5500/3K
3000	6663	54.1	123	VLX1/1500/6660/3K
4000	3891	30.7	127	VLX1/1500/3890/4K
4000	5295	40.9	130	VLX1/1500/5300/4K
4000	5805	45.5	128	VLX1/1500/5800/4K
4000	7023	54.1	130	VLX1/1500/7020/4K

OPTIONS

	PART CODE		PART CODE
DALI driver	/DD	4CMESH	/MM
3 Hour emergency	/E3S	4CMESH with Sensor	/MMS
3 hour DALI emergency	/E3D	Integrated DALI sensor	/IDS

EXAMPLE PART CODE: VLX1/1500/3890/4K/DD/E3D

Note: Tolerance range for optical and electrical data: $\pm 10\%$. 4C LIGHTING SOLUTIONS is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification.