

VandalLUX 4

400mm

- Wall mounted, vandal resistant, frame with stainless steel security screws
- Light Distribution: Direct/Asymmetrical
- Optical System: Opal Polycarbonate Diffuser
- Housing: Zinc Plated Steel
- Colour: White



TECHNICAL DATA SHEET

ELECTRICAL DATA

Main Voltage:	220-240V, 0/50/60Hz
Power Factor:	>0,90
Integrated Sensor:	Available

System power*, W:	10.2w to 12.8w
Control gear:	ECG On/off or Dali

LIGHTING DATA

Luminaire output*,lm(ta+25°C):	1146 to 1526
CRI (Ra):	80+
SDCM:	3
Distribution Type:	Direct
UGR Index:	<22

System efficacy, lm/W:	Up to 119
CCT, K:	3000 to 4000
Light Distribution:	Asymmetrical
Beam angle, °:	Asymmetrical
LED lifetime, h:	100000/L80B10

TECHNICAL DATA

Dimensions, mm:	L:380 W:110 H:150
Net weight, kg:	3

Quantity in package, pcs:	1
---------------------------	---

STANDARDS

Operating temperature range, °C:	ta -20... +40
Ingress protection code:	IP65

Mechanical impact resistance:	IK10
Certificates:	CE, UKCA, RoHS

Note: Tolerance range for optical and electrical data: $\pm 10\%$. 4C LIGHTING SOLUTIONS is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification.

